

GRAPHICS - Overlaminating Films

Issue date : 05/01/2005
Date last modification : 12/12/2016**4-GL3B-04065 RI-1867 GLOSS CLEAR AP PERMANENT WG62****Face Material**

Gloss clear monomeric vinyl film.

Type	Monomeric vinyl	
Colour and Finish	Gloss clear	
Weight	93 g/m ² ±10%	ISO-536
Thickness	70 μ ±10%	ISO 534-80

Adhesive

Acrylic permanent adhesive featuring high clarity and very high cohesion. Designed for a wide variety of substrates such as glass, ABS, PS, PVC. Unsuitable for apolar surfaces (like PE and PP).

Reference	AP permanent
Type	Acrylic permanent
Min. Appl. Temp.	+10°C
Service Temp.	-30°C/+120°C
Shear	Medium
Tack	Medium N/inch ²
Final Adhesion	High N/inch

Liner

Type	One side siliconised Glassine	
Colour and Finish	White	
Weight	62 g/m ² ±10%	PP-032 - ISO 536
Thickness	55 μ ±10%	ISO 534
Transparency	>45 %	DIN 53 147-64

Applications

Economy indoor/outdoor general purpose overlaminating film - gloss finish.

Printing Methods

Not printable.
Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

