

## Technical Data Sheet

**GRAPHICS** - Wide Format Ink Jet Print Media

Issue date : 05/11/2008 Date last modification : 25/05/2016

# 04239 RI-JET 100 GLOSS WHITE AP PERMANENT/BLACKOUT WK135

# Face Material

Gloss white monomeric vinyl film.

Type Colour and Finish Weight Thickness 
 Monomeric vinyl

 Gloss white

 134 g/m² ±10%
 ISO-536

 100 µ ±10%
 ISO 534-80

## <u>Adhesive</u>

Acrylic permanent adhesive with black pigmentation featuring very high cohesion. Designed for a wide variety of substrates such as glass, ABS, PS, PVC. Unsuitable for apolar surfaces (like PE and PP).

Reference Type Min. Appl. Temp. Service Temp. Shear Tack Final Adhesion AP permanent BLACK Acrylic permanent +10°C -30°C/+120°C Medium Medium N/inch<sup>2</sup> High N/inch

#### Liner

Туре	One side siliconised clay coated	
	Kraft	
Colour and Finish	White	
Weight	135 g/m²	PP-032 - ISO
	±10%	536
Thickness	145 µ ±10%	ISO 534
Transparency	n.a. %	DIN 53 147-64

#### **Applications**

For advertising and promotional applications (outdoor and indoor posters, billboards and signs) and for vehicle applications (flat sided including buses, trams and taxis).

## Printing Methods

The RI-JET series of ink-jet print media gives excellent print results with UV, solvent and eco-solvent ink-jet printing. Testing for suitability between media, printers and inks is always recommended prior to use.

## Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **<u>STORAGE CONDITIONS</u>**:

- This material must be stored at a temperature of  $~22^\circ\text{C}$   $\pm~2^\circ\text{C}$  and 50  $\pm~5\%$  of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.



Ritrama S.p.A. Via Senatore Simonetta, 24 20867 Caponago (MB) ITALN e-mail:info@ritrama.com w w w . r i t r a m a . c o m

